

ELECTROLYSIS SYSTEMS DOCUMENTATION



SDWT-20 - SDWT-100

SPECIFICATIONS

SPECIFICATIONS	SDWT-20	SDWT-30
Max. capacity g/Aktivchlor/h	ca. 20	ca. 30
Max. capacity kg/Aktivchlor/day	ca. 0.5	ca. 0.7
chlorine concentration g/l	ca. 2.5	ca. 2.5
water consumption l/h	ca. 20	ca. 20
salt consumption in kg/kg chlorine	ca. 2.8	ca. 2.8
power connection	230V 50 Hz	230V 50 Hz
power consumption kWh/kg chlorine	ca. 4	ca. 4
power consumption kVa	ca. 0.2	ca. 0.3
dimension (BxTxH) mm	400x850x1050	400x850x1050
empty kg	ca. 30	ca. 30
Tank Capacity in kg Salt	ca. 50	ca. 50
hydrogen separator	Typ-S	Typ-S
chlorine outlet Ø in mm	16	16
water inlet Ø in mm	16	16
drainage Ø in mm	16	16
display size	4" Touch Display	4" Touch Display
language	DE EN IT NL FR DK	

SPECIFICATIONS	SDWT-50	SDWT-100
Max. capacity g/Aktivchlor/h	ca. 50	ca. 100
Max. capacity kg/Aktivchlor/day	ca. 1.2	ca. 2.4
chlorine concentration g/l	ca. 2.5	ca. 2.5
water consumption l/h	ca. 20	ca. 40
salt consumption in kg/kg chlorine	ca. 2.8	ca. 2.8
power connection	230V 50 Hz	230V 50 Hz
power consumption kWh/kg chlorine	ca. 4	ca. 4
power consumption kVa	ca. 0.5	ca. 1.0
dimension (BxTxH) mm	450x850x1050	450x850x1050
empty kg	ca. 30	ca. 40
Tank Capacity in kg Salt	ca. 50	ca. 50
hydrogen separator	Typ-S	Typ-M
chlorine outlet Ø in mm	16	16
water inlet Ø in mm	16	16
drainage Ø in mm	16	16
display size	4" Touch Display	4" Touch Display
language	DE EN IT NL FR DK	