SWISSD&WTECH®
disinfection & water technology

ELECTROLYSIS SYSTEMS DOCUMENTATION

SDWT L-1000 - SDWT L-1800

VERSION 2026

SPECIFICATIONS

Specifications	SDWT L-1000 B1	SDWT L-1200 B1
Max. capacity g/Aktivchlor/h	ca. 1000	ca. 1200
Max. capacity kg/Aktivchlor/day	ca. 24	ca. 29
chlorine concetration g/l	ca. 4	ca. 4
waterinlet l/h	ca. 320	ca. 320
salt consumption in kg/kg chlorine	ca 2.8	ca. 2.8
power connection	400V | 50 Hz | 3x25 A [C]	400V | 50 Hz | 3x25 A [C]
power consumption kWh/kg chlorine	ca. 4	ca. 4
power consumption kVa	ca. 10	ca. 12
dimension (HxWxD)	1950x1100x750	1950x1100x750
Tank Capacity in kg Salt	ca. 500	ca. 500
hydrogen separator	Type L	Type L
chlorine outlet Ø in mm	1x 40	1x 40
waterinlet Ø in mm	40	40
drainage Ø in mm	20	20
Display size	10" Touch Display	
language	DE | EN | IT | NL | FR | DK	

Specifications	SDWT L-1500 B1	SDWT L-1800 B1
Max. capacity g/Aktivchlor/h	ca. 1500	ca. 1800
Max. capacity kg/Aktivchlor/day	ca. 36	ca. 44
chlorine concetration g/l	ca. 4	ca. 4
waterinlet l/h	ca. 400	ca. 480
salt consumption in kg/kg chlorine	ca. 2.8	ca. 2.8
power connection	400V | 50 Hz | 3x25 A [C]	400V | 50 Hz | 3x25 A [C]
power consumption kWh/kg chlorine	ca. 4	ca. 4
power consumption kVa	ca. 15	ca. 18
dimension (HxWxD)	1950x1100x750	1950x1100x750
Tank Capacity in kg Salt	ca. 500	ca. 500
hydrogen separator	Type L	Type L
chlorine outlet Ø in mm	1x 40	1x 40
waterinlet Ø in mm	40	40
drainage Ø in mm	20	20
Display size	10" Touch Display	
language	DE | EN | IT | NL | FR | DK	

SWISS D&W TECH AG **+41 71 375 66 30**

DORFSTRASSE 21, CH-9621 OBERHELFENSCHWIL